

PALAYESH PARAFFIN KHAVARAN

PRODUCT DATA SHEET

PRODUCT PROUP	SLACK WAX	PRODUCT NAME
WAX	GRADE PM	SW-PM

PRODUCT

Palayesh Paraffin Khavaran, PM are by product from solvent de-waxing process, provide a broad range of melting points and physical and performance characteristics that are suitable for use in various product and process applications.

APPLICATION

PM is the microcrystalline wax separated from raffinate of DAO solvent de-waxing unit.

Raw material for producing Vaseline, candles, chewing gum and useful for cosmetics, personal care and food contact applications.

PERFORMANCE BENEFITS

Odorless and tasteless.

Protection against moisture and corrosion.

High melting points.

CHARACTRESTICS	UNIT	TYPICAL	TEST METHOD
KINEMATIC VISCOSITY @ 100 °C	cST	17	ASTM: D-445
FLASH POINT	°C	300	ASTM: D-92
SPECIFIC GRAVITY @ 25°C	-	0.925	ASTM: D-190
OIL CONTENT	WT%	15	ASTM: D-721
CONGEALING POINT	°C	69	ASTM: D-937
COLOR	-	2.5	ASTM: D-1500
PENETRATION @ 25°C	0.1mm	68	ASTM: D-1321

WEST 3RD FLOOR, NO 251, SHAHID BEHESHTI AVE, ABBASABAD AVE , TEHRAN, IRAN

TEL: +982188500600

EMAIL: INFO@KHAVARANPARAFFIN.COM

M: +989101450130