

PALAYESH PARAFFIN KHAVARAN

PRODUCT DATA SHEET

PRODUCT GROUP	SLACK WAX	PRODUCT NAME
WAX	GRADE SW-10	SW-10

PRODUCT

Palayesh Paraffin Khavaran, **SW** are by product from solvent de-waxing process, provide a broad range of melting points and physical and performance characteristics that are suitable for use in various product and process applications.

APPLICATION

SW-10 is the slack wax separated from raffinate of DAO solvent de-waxing unit.

This product is used as blending components or waterproofing agents in the manufacture of various industrial products such as candles, polishes, matches, inks, carbon paper and externally can be applied as good dust suppressants or controlled-release agents for various chemical and fertilizers.

PERFORMANCE BENEFITS

Odorless and tasteless.

Protection against moisture and corrosion.

High melting points.

CHARACTRESTICS	UNIT	TYPICAL	TEST METHOD
KINEMATIC VISCOSITY @ 100 °C	cST	5	ASTM: D-445
FLASH POINT	°C	230	ASTM: D-92
SPECIFIC GRAVITY @ 25°C	-	0.825	ASTM: D-190
OIL CONTENT	WT%	15	ASTM: D-721
CONGEALING POINT	°C	55	ASTM: D-937
COLOR	-	1	ASTM: D-1500
DROP MELTING POINT @ 25°C	0.1mm	57	ASTM: D-127

WEST 3RD FLOOR, NO 251, SHAHID BEHESHTI AVE, ABBASABAD AVE , TEHRAN, IRAN

TEL: +982188500600

EMAIL: INFO@KHAVARANPARAFFIN.COM

M: +989101450130